


Product Benefits



No soaking required



Use non woven wallpaper adhesive



Wall adhesion technique



Covers over cracks



Knock-resistant



PVC-free



Highly flame retardant



Dry-strippable



Light-resistant



Washable

Processing

1a. Apply the paste to the wall. No soaking is required.



4. Trim wallpaper at ceiling, skirting boards, windows etc. using a straight edge and papering knife.

1b. Alternatively, use a pasting machine or paste table. Use non woven wallpaper adhesive.



5. Do not overlap on external corners, trim to size to produce a butt joint.

2. Hang the wallpaper tightly butted together at the edges.



6. The wallpaper is completely dry-strippable during later renovation work.

3. Smooth down the wallpaper using a sponge roller.



Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-ColorVlies

Raw materials/manufacture

ERFURT-ColorVlies is a hard-wearing wall covering, manufactured from special cellulose and textile fibres combined with polymer binding agents in a special embossing process.

All ERFURT-ColorVlies wall coverings are manufactured in the same production process and only vary in terms of their design.

Product data

- Roll dimensions 10.05 m long x 0.53 wide
- Carton content 12 rolls
- Edge-trimmed and packed in foil

Product characteristics

- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02 m
- Highly flame retardant as per DIN 4102-B1 in combination with mineral base surfaces
- Free from PVC, hazardous softeners and solvents
- Free from glass fibre
- Without added heavy metal compounds and formaldehyde
- Dimensionally stable and covers over cracks
- Fully dry-strippable

Application/processing

ERFURT-ColorVlies can be used on all indoor base surfaces suitable for wallpapering. The base surface should be plain-coloured before wallpapering with ERFURT-ColorVlies. Pre-coat the unfinished wall with a pigmented primer if required.

Application

For application, use a nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l or Metylan Direct in the ratio 1:17,5 = 200 g in 3 1/2 l of water) or a comparable product. Please also observe the processing instructions of the adhesive manufacturers.

The adhesive is applied evenly to the base surface and the cut widths laid dry in the adhesive bed (wall adhesion technique). Alternatively, ERFURT-ColorVlies can also be pasted using the pasting device, folded together and applied without soaking.

Adhesive

ERFURT-ColorVlies perpendicular with butt joint. Press the widths free of bubbles using a rubber roller or a straight edge. Push protruding material on ceilings, skirting, windows etc. into the corner with a straight edge and trim with a cutter knife. Do not stick the wall covering overlapping.

Painting

ERFURT-ColorVlies can be painted over when you come to redecorate.

Dry-strippable

ERFURT-ColorVlies is fully dry-strippable during later renovation.

Ingredients/test results

ERFURT-ColorVlies is regularly tested in accordance with the Food and Items of Daily Use Law § 30 and § 31.

The clearance certification (20535 U 04 of ISEGA-Forschungsund Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT-ColorVlies conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).

The water-vapour permeability has been determined by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg, as per DIN 52615 Part 1 with test report no. 1743/32.