

## Product Description

### Manufacturer

Erfurt & Sohn KG  
Hugo-Erfurt-Straße 1  
42399 Wuppertal  
www.erfurt.com

### Product designation

Erfurt KlimaTec System Adhesive

### Raw materials/Manufacture

ERFURT KlimaTec System Adhesive is a polyvinyl acetate polymer-based emulsion adhesive, which has excellent adhesion.

### Product data

Erfurt KlimaTec System Adhesive is supplied in 10 kg tubs.

### For use indoors

- For use indoors
- Excellent adhesion
- Simple and smooth to apply with a long-pile lambskin roller
- Simple, quick and clean to use
- Optimum adhesion to the base surface
- Excellent wet strength
- Excellent wallpapering results
- 20 minute working time
- No addition of heavy metal compounds
- Its water vapour permeability conforms to DIN 52615, corresponding to a diffusion-equivalent air layer thickness of 0.5 m (DIN EN ISO 7783-2), depending on the system

## Application/Handling

ERFURT KlimaTec System Adhesive has been specifically developed for use with the ERFURT SanReMo system. It can be used with all solid smooth or slightly textured base surfaces on interior walls and ceilings.

### Base surface

The base surface should be dry, clean and firm. Older finishes, which are no longer adhering to the wall or ceiling, should be removed. Serious differences in height should be levelled using a filler.

### Working conditions

Use between 0.3 and 0.5 kg/m<sup>3</sup>, depending on the base surface. The working temperature should not fall below 10°C. The working time, at normal temperature and under normal humidity conditions, is approximately 20 minutes.

### Adhesion



Evenly apply ERFURT KlimaTec System Adhesive to the base surface using a long-pile roller over an area measuring the width of 1 or 2 strip.



Place the wall covering onto the adhesive and press down with a wallpapering palette knife so that the adhesive is evenly distributed and a flat base surface is achieved.

### Drying

Allow to dry at +20 °C and at 65% relative air humidity and paint after 6 - 12 hours. This time may be longer at lower temperatures and with higher air humidity.

### Cleaning your tools

Wash with water immediately after use.

### Storage

ERFURT KlimaTec System Adhesive containers should be well sealed and stored in a cool and frost-free place. Protect from direct sunlight; possibly cover opened containers with a little water. Can be stored for at least two years in its sealed original container

### Disposal

Dispose of dried or hardened remains of ERFURT KlimaTec System Adhesive with normal household waste.