



Product advantages



No soaking required



'Paste the wall' technique



Easy to repaint



Low paint consumption



Knock-resistant



Covers over cracks



Breathable



PVC-free



High flame-retardant



Dry-strippable



For walls and ceilings



Nonwoven adhesive

Processing

1a. Use a pasting machine or paste table. No soaking is required or



4. Trim wallpaper at the ceiling, skirting boards, windows etc. using a straight edge and papering knife.

1b. apply the paste to the wall. No soaking is required. Use non woven wallpaper adhesive.



5. Trim into corners.

2. Hang the wallpaper tightly butted together at the edges.



6. After drying, the wallpaper surface can be creatively designed by applying either a colourful paint coating or plaster.

3. Smooth down the wallpaper using a sponge roller.



7. During subsequent renovations, wallpaper is dry-strippable, even when coated with plaster.

Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
D-42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-Trendvlies®Flat

Raw materials/manufacture

ERFURT-Trendvlies®Flat is a smooth wallcovering that is produced using special wood pulp and textile fibres, in combination with polymer binding agents.

Product data

- The roll dimensions are 20.00 m long x 0.75 m wide
- Carton content: 6 rolls
- Weight: approx. 140 g/m²
- Trimmed edges and packaged in shrink wrap

Product characteristics

- Conceals color irregularities on the base surface well enough that only one coat of paint is necessary in many cases.
- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of approx. 0.02 m.
- ERFURT-Trendvlies®Flat conforms to DIN 4102-B1 "highly flame retardant." The compound is non-flammable on mineral base surfaces.
- Maintains dimensions and covers over cracks.
- The surface is very hard-wearing in combination with the corresponding coating materials.
- Free from PVC, softeners, and solvents
- Free from glass fibre
- Without added heavy metal compounds and formaldehyde
- Can be painted over several times with normal, commercially available paints

Application/processing

ERFURT-Trendvlies®Flat can be used on all indoor base surfaces suitable for wallpapering. The base surface must be dry, clean, sturdy, and smooth, with low absorbency. Completely remove all old wallpaper and non-adherent coatings. Smooth rough base surfaces with gypsum plaster. Use solvent-free primer to prime absorbent base surfaces.

Using wall adhesion technique

For application, use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Apply adhesive evenly to the base surface and the cut widths laid dry in the adhesive bed. Please also observe the processing instructions of the adhesive manufacturers.

Using Pasting Machine

ERFURT-Trendvlies®Flat can also be pasted using the pasting machine, folded together and applied without soaking. For application, use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Please also observe the processing instructions of the adhesive manufacturers.

Adhesion

Apply ERFURT-Trendvlies®Flat perpendicular with butt joint. Press the widths free of bubbles using a rubber roller or a straight edge. Push protruding material on ceilings, skirting, windows etc. into the corner with a straight edge and trim with a cutter knife. Do not apply the wall covering such that it overlaps.

Immediately remove any adhesive stains from the surface of wallpaper.

On textured base surfaces

ERFURT-Trendvlies®Flat can also be used for the quick renovation of textured base surfaces (e.g. fibre glass), which must be prepped in one step for papering, plaster or paint. For this process, use a dispersion adhesive (e.g. Metalyn Ovalit P Styrofoam Adhesive or comparable.) Using a notched trowel apply adhesive evenly to the base surface. Lay the cut widths in the adhesive and using the straight edge press the widths, so that the adhesive is evenly distributed and a canvas-like base surface is created. Push protruding material on ceilings, skirting, windows etc. into the corner with a straight edge and trim with a cutter knife. Do not apply ERFURT-Trendvlies®Flat such that it overlaps.

Painting

After drying, ERFURT-Trendvlies®Flat must be painted or otherwise coated. Gloss paint, high quality dispersion paints, or plaster may be used. To achieve a glossy look, two coats of paint are required.

Dry-strippable

Whether painted, covered with wallhangings or layered with plaster, ERFURT-Trendvlies®Flat is completely dry-strippable during subsequent renovations.

Ingredients/test results

ERFURT-Trendvlies®Flat is regularly tested in accordance with the Food and Items of Daily Use Law § 30 and § 31.

The clearance certification (20534 U 04 of ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT-Trendvlies®Flat conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).

The water-vapour permeability has been determined as per DIN 52615 part 1 with test report no. 1743/32.