



Product Benefits



No soaking require




Use non woven wallpaper adhesive



Wall adhesion technique



For use on walls and ceilings



Covers over cracks



Knock-resistant



PVC-free



Highly flame retardant



Breathable



Dry-strippable

Processing

1a. Use a pasting machine or paste table.



4. Trim wallpaper at ceiling, skirting boards, windows etc. using a straight edge and papering knife.

1b. Alternatively, apply the paste to the wall. No soaking is required.



5. Do not overlap on external corners, trim to size to produce a butt joint.

2. Hang the wallpaper tightly butted together at the edges. Immediately remove any traces of adhesive from the surface.



6. Once dry, the surface can be given a creative finish with a conventional wall glaze.

3. Smooth down the wallpaper using a sponge roller.



7. The wallpaper is completely dry-strippable during later renovation work.

Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-MagicVlies

Raw materials/manufacture

ERFURT-MagicVlies are textured wall coverings, manufactured from special cellulose and textile fibres combined with polymer binding agents.

Product data

- Roll dimensions 10.05 m long x 0.75 wide
- Carton content 6 rolls
- Edge-trimmed and packed in foil

Product characteristics

- Suitable for use with all conventional wall glazes.
- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02 m
- Highly flame retardant as per DIN 4102-B1 in combination with mineral base surfaces
- Dimensionally stable and covers over cracks
- Very hard-wearing in combination with the corresponding coating materials
- Free from PVC, hazardous softeners and solvents
- Free from glass fibre
- Without added heavy metal compounds and formaldehyde

Application/processing

ERFURT-MagicVlies can be used on all indoor base surfaces suitable for wallpapering. The base surface must be dry, clean, sturdy, and smooth, with low absorbency. Completely remove all old wallpaper and non-adherent coatings. Smooth rough base surfaces with gypsum plaster. Use solvent-free primer to prime absorbent base surfaces.

Using wall adhesion technique

For application, use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Apply adhesive evenly to the base surface and the cut widths laid dry in the adhesive bed. Please also observe the processing instructions of the adhesive manufacturers.

Using Pasting Machine

ERFURT-MagicVlies can also be pasted using the pasting machine, folded together and applied without soaking. For application, use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Please also observe the processing instructions of the adhesive manufacturers.

Application

Apply ERFURT-MagicVlies perpendicular with butt joint. Press the widths free of bubbles using a rubber roller or a straight edge. Push protruding material on ceilings, skirting, windows etc. into the corner with a straight edge and trim with a cutter knife. Do not stick the wall covering overlapping. Immediately remove any traces of adhesive from the surface.

Painting

Once dry, ERFURT-MagicVlies should be painted or coated. Conventional wall glazes can be used for this.

Dry-strippable

ERFURT-MagicVlies is fully dry-strippable during later renovation.

Ingredients/test results

ERFURT-MagicVlies is regularly tested in accordance with the Food and Items of Daily Use Law § 30 and § 31.

The clearance certification (20535 U 04 of ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT-MagicVlies conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).

The water-vapour permeability has been determined by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg, as per DIN 52615 Part 1 with test report no. 1743/32.