



Product advantages




3 paper layers



Can be painted over easily with all emulsion paints



Low paste consumption



Covers over cracks



PVC-free



High embossing stability



Biodegradable



Water-vapour permeable




Easy to process



A good quality ready mixed or flake adhesive is recommended

Processing

1. The base surface must be dry, clean, firm, absorbent and smooth. Mark width of the fabric on the wall as a vertical line to aid hanging the first length perpendicular to the floor.



5. Let all the lengths soak for the same amount of time: 15 minutes.

2. A good quality ready mixed or flake adhesive is recommended. Mix to the manufacturer's instructions for embossed wallpapers.



6. Apply Novaboss®Pro seam to seam. Press free of bubbles and folds with wallpapering brush or sponge roller.

3. Cut the Novaboss to length making sure you have allowed for any pattern repeat.
a) Paste the lengths on a paste table or



7. Trim carefully into corners etc. using a straight edge and trimming knife or scissors.

b) use a pasting machine.



8. Do not overlap the paper at external corners.

4. The pasted lengths are folded 2/3 to 1/3. Do not crease when folding.



9. Following drying, we recommend a coat of high-quality latex paint. Use silk mat or silk gloss paints.

Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
D-42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-Novaboss®Pro

Raw materials/manufacture

ERFURT-Novaboss®Pro is a white, triple-layer, special embossed wallpaper.

The manufacturing process consists of two layers of paper being glued and embossed, and a third paper layer, which remains smooth, being laminated using a special process.

All ERFURT-Novaboss®Pro types are manufactured using the same production processes and differ only in terms of design.

No problems arise when removing/disposing of ERFURT-Novaboss®Pro, as the natural basic substances return themselves automatically to the ecological circular flow.

Characteristics

Thanks to the three layers of paper, ERFURT-Novaboss®Pro has a particularly stable structure and is very insensitive to pressure during processing. The smooth reverse side results in a lower paste consumption than with embossed wallpaper.

The roll dimensions are 10.05 long x 0.53 m wide.

Carton content ERFURT-Novaboss®Pro:
4551, 4556, 4562, 4577, 4578: 9 rolls.
4559, 4561: 12 rolls.

The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of approx. 0.05 m.

ERFURT-Novaboss®Pro conforms to DIN 4102-B2 "normally flame retardant building materials".

Application/processing

ERFURT-Novaboss®Pro can be used on all indoor base surfaces suitable for wallpapering. Successful wallpapering is fundamentally dependent on the quality and the expert preparation of the base surface. The fundamental rule is: The base surface must be dry, good-bearing and evenly absorbent, clean and smooth.

For adhesion, use nonwoven adhesive (e.g. Metylan Secura 1:11 = 500 g in 5.5 l or Metylan NP New Plaster Paste 1:11 = 1,000 g in 11 l of water) or special paste (e.g. Metylan Special 1:20 = 200 g in 4 litres of water) or a comparable product. Please also observe the processing instructions of the adhesive manufacturers.

Paste the widths evenly, fold together and allow to soak for 15 minutes each. Do not bend the loops. Bubbles formed during wallpapering can be pulled smooth again following drying. Apply the wallpaper carefully with butt joint. Remove paste stains immediately.

ERFURT-Novaboss®Pro must be painted over following wallpapering and drying of the wallpaper. Silk-mat or silk-gloss latex paints as per DIN EN 13300 are best suited for this.

Ingredients/test results

ERFURT-Novaboss®Pro is made up of paper fibre, cellulose and auxiliary materials.

It is low in harmful substances, as only substances set out in the 36th Recommendation of the Synthetics Commission of the Federal Health Office for food packaging from paper, cardboard and paperboard are used in production.

The clearance certification (20536 U 04 of ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT Novaboss®Pro conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).

The water-vapour permeability has been determined by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg, as per DIN 52615 with test report no. 1743/32.