

Product Description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
42399 Wuppertal
www.erfurt.com

Product designation

Erfurt System Adhesive SR 2

Raw materials/Manufacture

ERFURT System Adhesive SR 2 is a polyvinyl acetate polymer-based emulsion adhesive, specifically developed for use with SanReMo, which has excellent adhesion.

Product data

ERFURT System Adhesive SR2 is supplied in 18 kg tubs.

For use indoors

- For use indoors
- Excellent adhesion
- Simple and smooth to apply with a long-pile lambskin roller
- Sprayable with an airless unit
- Simple, quick and clean to use
- Optimum adhesion to the base surface
- Excellent wet strength
- Excellent wallpapering results
- 20 MINUTE WORKING TIME
- No addition of heavy metal compounds
- Its water vapour permeability conforms to DIN 52615, corresponding to a diffusion-equivalent air layer thickness of 0,07 m (DIN EN ISO 7783-2), depending on the system

Application/Handling

ERFURT System Adhesive SR 2 has been specifically developed for use with the ERFURT SanReMo system. It can be used with all solid smooth or slightly textured base surfaces on interior walls and ceilings.

Base surface

The base surface should be dry, clean and firm. Older finishes, which are no longer adhering to the wall or ceiling, should be removed. Serious differences in height should be levelled using a filler.

Working conditions

Use between 0.3 and 0.5 kg/m³, depending on the base surface. The working temperature should not fall below 10° C. The working time, at normal temperature and under normal humidity conditions, is approximately 20 minutes.

Adhesion



Evenly apply ERFURT System Adhesive SR 2 to the base surface using a long-pile roller over an area measuring the width of 1 or 2 strips.



Place the wall covering onto the adhesive and press down with a wallpapering palette knife so that the adhesive is evenly distributed and a flat base surface is achieved.

Drying

Allow to dry at +20 °C and at 65% relative air humidity and paint after 6 - 12 hours. This time may be longer at lower temperatures and with higher air humidity.

Cleaning your tools

Wash with water immediately after use.

Storage

ERFURT System Adhesive SR2 containers should be well sealed and stored in a cool and frost-free place. Protect from direct sunlight; possibly cover opened containers with a little water. Can be stored for at least one year in its sealed original container

Disposal

Dispose of dried or hardened remains of ERFURT System Adhesive SR2 with normal household waste.

Contents/Test results

Its water vapour permeability conforms to DIN 52615, corresponding to a diffusion-equivalent air layer thickness of 0.25 - 0.40 m (DIN EN ISO 7783-2), depending on the configuration of the system.