


Product advantages



No soaking required



'Paste the wall' technique



Low paint consumption



Knock-resistant



Covers over cracks



PVC-free



Highly flame-retardant



Use non woven 'paste the wall' wallpaper adhesive

Processing

- 1a.** Apply the paste to the wall.
No soaking is required.
Use non woven wallpaper adhesive



- 4.** Trim wallpaper at the ceiling, skirting boards, windows etc. using a straight edge and papering knife.

- or **1b.** use a pasting machine or paste table.



- 5.** Trim into corners.

- 2.** Hang the wallpaper tightly butted together at the edges.



- 6.** After drying, paint over with a good quality emulsion paint.

- 3.** Smooth down the wallpaper using a sponge roller.



Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
D-42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-Vliesfaser®Basic

Raw materials/manufacture

ERFURT-Vliesfaser®Basic is a hard-wearing wall covering, manufactured from special cellulose and textile fibres, combined with polymer binding agents and using a special embossing technique.

All ERFURT-Vliesfaser®Basic types are manufactured using the same production processes.

Product data

- Roll dimensions 10.05 m long x 0.53 wide
- Carton content 12 rolls
- Weight approx. 130 g/m²
- Edge-trimmed and packed in foil

Product characteristics

- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02 m
- Highly flame retardant as per DIN 4102-B1 in combination with mineral base surfaces
- Free from PVC, softeners, solvents and glass fibre
- Without added heavy metal compounds and formaldehyde
- Dimensionally stable and covers over cracks
- The surface of ERFURT-Vliesfaser® is very hard-wearing in combination with the corresponding coating materials
- Can be painted over several times with normal, commercially available paints

Application/processing

ERFURT-Vliesfaser®Basic can be used on all indoor base surfaces suitable for wallpapering.

For application, use a nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l or Metylan Direct in the ratio 1:17.5 = 200 g in 3 1/2 l of water) or a comparable product. Please also observe the processing instructions of the adhesive manufacturers.

The adhesive is applied evenly to the base surface and the cut widths laid dry in the adhesive bed (wall adhesion technique). Alternatively, ERFURT-Vliesfaser®Basic can also be pasted using the pasting device, folded together and applied without soaking.

Apply ERFURT-Vliesfaser®Basic perpendicular with butt joint. Press the widths free of bubbles using a rubber roller or a straight edge. Push protruding material on ceilings, skirting, windows etc. into the corner with a straight edge and trim with a cutter knife. Do not apply the wall covering overlapping.

ERFURT-Vliesfaser®Basic must be painted over. We recommend a good quality emulsion paint.

Ingredients/test results

ERFURT-Vliesfaser®Basic is regularly tested in accordance with the Food and Items of Daily Use Law § 30 and § 31.

The clearance certification (22409 U 06 of ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT Vliesfaser®Basic conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).

The water-vapour permeability has been determined by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg, as per DIN 52615 Part 1 with test report no. 1743/37.