


Product advantages



No soaking required




'Paste the wall' technique



Low paint consumption



Knock-resistant



Covers over cracks



PVC-free



Highly flame-retardant



Dry-strippable



Use non woven 'paste the wall' wallpaper adhesive

Processing

- 1a.** Apply the paste to the wall. No soaking is required. Use non woven wallpaper adhesive



- 4.** Trim wallpaper at the ceiling, skirting boards, windows etc. using a straight edge and papering knife.

- or **1b.** use a pasting machine or paste table for sticking.



- 5.** Trim into corners.

- 2.** Hang the wallpaper tightly butted together at the edges.



- 6.** After drying, paint over with a good quality emulsion paint.

- 3.** Smooth down the wallpaper using a sponge roller.



- 7.** The wallpaper is completely dry-strippable during later renovation work.

Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
D-42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-Vliesfaser®Design

Raw materials/manufacture

ERFURT-Vliesfaser®Design is a hard-wearing wall covering, manufactured from special cellulose and textile fibres, combined with polymer binding agents and manufactured using a special embossing technique.

All ERFURT-Vliesfaser®Design types are manufactured using the same production processes and differ only in terms of design.

Product data

- Roll dimensions 10.05 m long x 0.53 wide
- Carton content
 - ERFURT-Vliesfaser®Design 806, 808, 826 and 830: 9 rolls
 - ERFURT-Vliesfaser®Design 807: 12 rolls
 - ERFURT-Vliesfaser®Design 815: 16 rolls
- Weight approx. 160 g/m²
- Edge-trimmed and packed in foil

Product characteristics

- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02 m
- Highly flame retardant as per DIN 4102-B1 in combination with mineral base surfaces
- Free from PVC, softeners, solvents and glass fibre
- Without added heavy metal compounds and formaldehyde
- Dimensionally stable and covers over cracks
- The surface of ERFURT-Vliesfaser® is very hard-wearing in combination with the corresponding coating materials
- Can be painted over several times with normal, commercially available paints
- Fully dry-strippable

Application/processing

ERFURT-Vliesfaser®Design can be used on all indoor base surfaces suitable for wallpapering.

For application, use a nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l or Metylan Direct in the ratio 1:17.5 = 200 g in 3 1/2 l of water) or a comparable product. Please also observe the processing instructions of the adhesive manufacturers.

The nonwoven adhesive is applied evenly to the base surface and the cut widths laid dry in the adhesive bed (wall adhesion technique). Alternatively, ERFURT-Vliesfaser®Design can also be pasted using the pasting machine, folded together and applied without soaking.

Apply ERFURT-Vliesfaser®Design perpendicular with butt joint. Press the widths free of bubbles using a rubber roller or straight edge. Push protruding material on ceilings, skirting, windows etc. into the corner with a straight edge and trim with a cutter knife. Do not apply the wall covering overlapping

Following drying, ERFURT-Vliesfaser®Design must be painted over. We recommend a good quality emulsion paint.

Dry-strippable

ERFURT-Vliesfaser®Design is fully dry-strippable during later renovation.

Ingredients/test results

ERFURT-Vliesfaser®Design is regularly tested in accordance with the Food and Items of Daily Use Law § 30 and § 31.

The clearance certification (20535 U 04 of ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT Vliesfaser®Design conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).

The water-vapour permeability has been determined by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg, as per DIN 52615 Part 1 with test report no. 1743/32.