


Product advantages



No soaking required



'Paste the wall' technique



Less paint needed



Knock-resistant



Covers cracks



PVC-free



Flame-retardant



Use non woven 'paste the wall' wallpaper adhesive

Hanging instructions

1a. Use a pasting machine or paste table.



3. Smooth down the wallpaper using a sponge roller.

1b. Alternatively apply the paste to the wall. No soaking is required. Use non woven wallpaper adhesive.



4. Trim wallpaper at ceiling, skirting boards, windows etc. with a straight edge and papering knife.

2. Hang wallpaper tightly butted together at the edges.



5. Once the wallpaper has dried it can be painted over using emulsion paint.

Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
D-42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-Vliesfaser®Objekt

Raw materials/manufacture

ERFURT-Vliesfaser®Objekt is a hard-wearing wall covering, manufactured from special cellulose and textile fibres combined with polymer binding agents using a special embossing technique.

All ERFURT-Vliesfaser®Objekt varieties are manufactured using the same production process and differ only in terms of design.

Product data

- Roll dimensions 25.00 m long x 0.75 m wide
- Carton content 2 rolls
- Weight: approx. 130 g/m²
- Edge-trimmed and packed in foil

Product characteristics

- Water vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02 m
- Highly flame retardant in combination with mineral base surfaces as per DIN 4102-B1
- Free from PVC, softeners and solvents
- Free from glass fibre
- Without added heavy metal compounds and formaldehyde
- Dimensionally stable and bridges over cracks
- Very hard-wearing in combination with the corresponding coating materials
- Can be painted over several times with normal, commercially-available paints

Application/processing

ERFURT-Vliesfaser®Objekt can be used indoors on all base surfaces suitable for wallpapering. The BSF information leaflets nos. 7 and 16 must be observed.

Processing using wall adhesion technique

For sticking, use a fleece adhesive (e.g. Metylan NP new plaster paste in the ratio 1:10 = 1000 g in 10 l of water) or a comparable product. The adhesive/paste is applied evenly to the base surface and the cut widths laid dry in the adhesive/paste bed. Please also observe the processing instructions of the adhesive manufacturers.

Processing using the pasting device

Paste is applied to ERFURT-Vliesfaser®Objekt using the pasting device, the product is then folded together and can be stuck without soaking time. For sticking, fleece adhesive (e.g. Metylan NP new plaster paste in the ratio 1:10 = 1000 g in 10 l of water) or a comparable product should be used. Please also observe the processing instructions of the adhesive manufacturers.

Application

Apply ERFURT-Vliesfaser®Objekt perpendicular with butt joint. Press the widths free of bubbles using a rubber roller or a straight edge. Press protruding material on ceilings, skirting boards, windows etc. into the corner with a straight edge and trim with a cutter knife. Do not stick the wall covering overlapping.

Painting

Following drying, ERFURT-Vliesfaser®Objekt must be painted over. We recommend a good quality emulsion paint.

Ingredients/test results

ERFURT-Vliesfaser®Objekt is regularly tested in accordance with the Food and Items of Daily Use Law § 30 and § 31.

The clearance certificate (22409 U 06 of ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT-Vliesfaser®Objekt conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).

The water vapour permeability has been determined by ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg, as per DIN 52615, part1, with test report no. 1743/37.