


Product advantages



No soaking required



'Paste the wall' technique



Knock-resistant



Can be painted over several times with all latex paints



Evens out unevenness and hairline cracks



Highly tear-resistant



PVC-free



Active-breathing



Dry-strippable



Use non woven 'paste the wall' wallpaper adhesive

Processing

1a. Use a pasting machine or paste table.



4. Trim wallpaper at the ceiling, skirting boards, windows etc. using a straight edge and trimming knife.

1b. Alternatively apply the paste to the wall. No soaking is required. Use non woven wallpaper adhesive.




5. Trim into corners.

2. Hang the wallpaper tightly butted together at the edges.



6. After drying, paint over with a good quality emulsion paint.

3. Smooth down the wallpaper using a sponge roller.



7. The wallpaper is completely dry-strippable during later renovation work.

Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
D-42399 Wuppertal
www.erfurt.com

Product designation

ERFURT-Rauhvlies®

Raw materials/manufacture

ERFURT-Rauhvlies® is a wall covering consisting of several layers, into which the structure-forming wood fibres are firmly incorporated.

ERFURT-Rauhvlies® is made up of cellulose, textile fibres and polymer binding agents, and is produced on the paper machine using a special technique.

The material can be composted as it is predominantly decomposable.

The roll dimensions are 10.05 long x 0.53 m wide.
Carton content 12 rolls

Characteristics

- Edge-trimmed and packed in foil
- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of approx. 0.02 m
- Conforms to DIN 4102-B2 "normally flame retardant building materials".
- **Free from** PVC, softeners and solvents
- **Free from** glass fibre
- Without added heavy metal compounds and formaldehyde
- **Dimensionally stable** thanks to fibre reinforcement and special impregnation
- **Extremely hard-wearing, covers over cracks and is structurally stable**
- Conforms to DIN EN 234 (recommendations on wall coverings for retrospective treatment)
- **Dry-strippable**

Application/processing

ERFURT-Rauhvlies® can be used on all indoor base surfaces suitable for wallpapering.

Base surface

The base surface must be dry, clean, firm, absorbent and smooth. Remove old wallpaper and non-adhering paint. Smooth rough base surfaces with gypsiferous filler. Pre-glue smooth gypsum plaster with diluted paste. Heavily absorbent base surfaces must be primed with solvent-free base paints. When applying using wall adhesion technique, even absorption is important.

Processing using wall adhesion technique

For application, use a nonwoven adhesive (e.g. Metylan Secura 1:11 = 500 g in 5.5 l or Metylan Direct in the ratio 1:17.5 = 200 g in 3 1/2 l of water) or a comparable product. Apply the paste generously and evenly to the base surface over the width of the fabric and lay the cut widths dry in the adhesive. Please also observe the processing instructions of the adhesive manufacturers

Application

Apply ERFURT-Rauhvlies® perpendicular with butt joint. Press the widths free of bubbles using a rubber roller or a straight edge. Push protruding material on ceilings, skirting, windows etc. into the corner with a straight edge and trim with a knife. Do not stick the wall covering overlapping.

Painting

After drying, ERFURT-Rauhvlies® must be coated with the corresponding paints as per DIN EN 13300.

Dry-strippable

ERFURT-Rauhvlies® is fully dry-strippable during later renovation.

Ingredients/test results

ERFURT-Rauhvlies® is regularly tested in accordance with the Food and Items of Daily Use Law §§ 30 and 31.

The clearance certification (21217 U 05 of ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH, Aschaffenburg) confirms that ERFURT Rauhvlies® conforms to the regulations of the Food and Items of Daily Use Law, as well as to the 36th Recommendation of the Federal Health Office (BGA).