













Product advantages

	No soaking required		'Paste the wall'		Easy to paint		Economical paint surface
	Knock-resistant		Covers cracks		Active-breathing		PVC-free
	Flame retardant		Dry-strippable, easy to remove		For walls and ceilings		Nonwoven adhesive

Hanging instructions

1a. Use a pasting machine or paste table – no soaking required or



4. Trim off the excess material with a knife and a straight edge where it meets the ceiling, skirting boards or windows.

1b. paste the wall' and apply. No soaking required.



5. Trim the wallpaper at corners and edges and butt the next length up to it.

2. Butt the lengths together.



6. Allow to dry before applying a good quality emulsion paint (DIN EN 13300), plaster or wallpaper.

3. Smooth down the wallpaper using a sponge roller.



7. The wallpaper can easily be dry-stripped when the time comes to redecorate.

Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
42399 Wuppertal
www.erfurt.com

Product name

ERFURT-Variolvies® M 160

Raw materials/Manufacture

ERFURT-Variolvies® M 160 is a smooth wall covering, manufactured from special cellulose and textile fibres, combined with polymer binding agents.

Product data

- Order no. 750
- Roll dimensions: 25 m long x 0.75 m wide
- Carton content: 2 rolls
- Weight: approx. 160 g/m²
- Edge-trimmed and wrapped in film

Product features

- Good performance on base surfaces with a variety of paint finishes
- In most circumstances one coat of paint is enough to produce an excellent finish
- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02m
- Highly flame retardant as per DIN 4102-B1 when used on mineral base surfaces
- Does not contain PVC, softeners and solvents
- Does not contain fibre glass
- Does not contain heavy metal compounds and formaldehyde
- Dimensionally stable and covers over cracks
- Very hard-wearing when used with an appropriate paint
- Dry-strippable when applied with the appropriate 'paste the wall' adhesive
- Produces a sound base for paint, printed wallpaper or plaster
- Can be painted over several times with commercial paints

Product description

ERFURT-Variolvies® M 160 as a base surface for painting:

Excellent performance, even on old, cracked plaster or similar which is to be painted after preparation. Also creates a smooth flat surface where the base surface is made up of a variety of different materials e.g. plaster, exposed concrete or plasterboard.

Use nonwoven adhesive (e.g. Metylan NP New Plaster Paste in a ratio of 1:10 i.e. 1 kg in 10 l water or Metylan NP Power Granulate Plus in a ratio of 1:12 i.e. 1 kg in 12 litres of water or when using 'paste the wall' technique in a ratio of 1:10 i.e. 1 kg in 10 l water) or a similar good quality paste suitable for 'paste the wall' products.

ERFURT-Variolvies® M 160 does not need soaking before hanging. Hang ERFURT-Variolvies® M 160 vertically using butt joints. Use either a water or shower-proof emulsion paint (DIN EN 13300) when appropriate for the room in which the wall covering will be used.

ERFURT-Variolvies® M 160 is also an ideal base surface for creative design using wax glaze, plaster or filler.

ERFURT-Variolvies® M 160 as a base surface for wallpaper:

ERFURT-Variolvies® M 160 gives a smooth base surface suitable for almost any type of wall covering. Use the adhesive prescribed for the particular wall covering, however we recommend that at the very least, paste in a ratio of 1:20 (200g in 4 litres water) is used in this application. Thanks to the stability of ERFURT-Variolvies® M 160, all wall coverings pasted on top of it can be removed at a later stage without damaging the base surface.

ERFURT-Variolvies® M 160 can be covered again and again.

ERFURT-Variolvies® M 160 for speedy redecoration:

Filled dispersion adhesive i.e. Metylan Ovalit P or similar should be used when covering structured base surfaces, such as fibreglass with ERFURT-Variolvies® M 160 to produce a flat surface. Evenly apply adhesive to the base surface using a toothed spatula. Lay the cut lengths in the adhesive and press down with a spatula so that the adhesive is evenly distributed and a smooth base surface is achieved. Press excess paper into the corners under ceilings, at skirting and windows using the spatula and trim with a knife. Do not overlap ERFURT-Variolvies® M 160.

ERFURT-Variolvies® M 160 for 'problem surfaces':

Use 'paste the wall' technique combined with Metylan Ovalit V to achieve a smooth finish over 'problem surfaces' such as varnished, synthetic finishes.

Dry-strippable

ERFURT-Variolvies® M 160 is fully dry-strippable when later redecorating (not, however Metylan Ovalit V or Ovalit P).

Ingredients/Test Results

ERFURT-Variolvies® M 160 is regularly tested in accordance with the Food and Consumer Goods Act § 30 and § 31.

The Declaration of No Objection (20535 U 04 by the ISEGA Research and Testing Co.Ltd., Aschaffenburg) confirms that ERFURT-Variolvies® M 160 meets the requirements of the Food and Consumer Goods Act as well as Recommendation 36 of the Federal German Office of Health.

The water vapour permeability was determined by Test Report No. 1743/32 in accordance with DIN 52615 Part 1.