



Product advantages



No soaking required



'Paste the wall'



Easy to paint



Economical paint surface



Knock-resistant



Covers cracks



Active breathing



PVC free



Flame retardant



Easy to remove



Nonwoven adhesive

Hanging instructions

1a. Use a pasting machine or paste table – no soaking required or



4. Trim off excess material with a knife and a straight edge where it meets the ceiling, skirting boards or windows.

1b. paste the wall and apply. No soaking required.



5. Trim the wallpaper at corners and edges and butt the next length up to it, avoid overlapping.

2. Butt the lengths together.



6. Allow to dry before applying good quality emulsion paint (DIN 13300). Alternatively use as a base for plaster or wallpaper.

3. Smooth down the wallpaper using a sponge roller.



Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
42399 Wuppertal
www.erfurt.com

Product name

ERFURT-Variovlies M 120

Raw materials/Manufacture

ERFURT-Variovlies M 120 is a flat wall covering, manufactured from special cellulose and textile fibres, combined with polymer binding agents.

Product data

- Roll dimensions: Order no. 760, 50 m long x 0.75 m wide
- Roll dimensions: Order no. 763, 25 m long x 1.00 m wide
- Carton content: 2 rolls (Order no. 760)
- Carton content: 4 rolls (Order no. 763)
- Weight: approx. 120 g/m²
- Edge-trimmed and wrapped in film

Product features

- Good performance on base surfaces with a variety of paint finishes
- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02m
- Highly flame retardant as per DIN 4102-B1 when used on mineral base surfaces
- Does not contain PVC, softeners or solvents
- Does not contain fibre glass
- Does not contain heavy metal compounds or formaldehyde
- Dimensionally stable and covers over cracks
- Very hard-wearing when used with an appropriate paint
- Easily removable when wet
- Can be painted over several times with commercial paints

Application/Hanging

ERFURT-Variovlies M 120 as a base surface for painting:

Suitable for use even on old and cracked plaster or similar which is to be painted after preparation. Ideal for creating smooth surfaces for painting where the base surface is made up of a variety of different materials e.g. plaster, exposed concrete or plasterboard.

Use nonwoven adhesive (e.g. Metylan NP New Plaster Paste in a ratio of 1:10 i.e. 1 kg in 10 l water or Metylan NP Power Granulate Plus in a ratio of 1:12 i.e. 1 kg in 12 l water or using paste the wall technique in a ratio of 1:10 i.e. 1 kg in 10 l water) or a similar good quality paste suitable for 'paste the wall' products.

ERFURT-Variovlies M 120 does not need to be soaked before hanging. Hang ERFURT-Variovlies M 120 vertically using butt joints. Use a good quality emulsion paint including water or shower-proof emulsion paint (DIN EN 13300) when appropriate.

ERFURT-Variovlies M 120 as a base surface for all types of wallpaper:

Use adhesive suitable for the particular wall covering, however we recommend that at the very least, paste at a ratio of 1:20 (200g in 4 l water), for this application. Thanks to the stability of ERFURT-Variovlies M 120, all wall coverings applied over it can be removed when later redecorating without damaging the base surface.

ERFURT-Variovlies M 120 can be covered again and again.

Easy to remove

ERFURT-Variovlies M 120 can be easily removed after soaking.

Ingredients/Test Results

ERFURT-Variovlies M 120 is regularly tested in accordance with the Food and Consumer Goods Act § 30 and § 31.

The Declaration of No Objection (20535 U 04 by the ISEGA Research and Testing Co.Ltd., Aschaffenburg) confirms that ERFURT-Variovlies M 120 meets the requirements of the Food and Consumer Goods Act as well as Recommendation 36 of the Federal German Office of Health.

The water vapour permeability was determined by Test Report No. 1743/32 in accordance with DIN 52615 Part 1.