


Product advantages



No soaking required



'Paste the wall'



Easy to paint



Economical paint surface



Knock-resistant



Covers cracks



Active-breathing



PVC-free



Flame retardant



Easy to remove



Nonwoven adhesive

Hanging instructions

1a. Use a pasting machine or paste table – no soaking required or



4. Trim off the excess material with a knife and a straight edge where it meets the ceiling, skirting boards or windows.

1b. paste the wall and apply. No soaking required.



5. Trim the wallpaper at corners and edges and butt the next length up to it, avoid overlapping.

2. Butt the lengths together.



6. Allow to dry before applying good quality emulsion paint (DIN 13300). Alternatively, use as a base for plaster or wallpaper.

3. Smooth down the wallpaper using a sponge roller.



Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
42399 Wuppertal
www.erfurt.com

Product name

ERFURT-Variovlies® M 140 Objekt

Raw materials/Manufacture

ERFURT-Variovlies® M 140 Objekt is a flat wall covering, manufactured from special cellulose and textile fibres, combined with polymer binding agents.

Product data

- Order no. 741
- Roll dimensions: 25 m long x 1.0 m wide
- Carton content: 2 rolls
- Weight: approx. 140 g/m²
- Edge-trimmed and wrapped in film

Product features

- Good performance on base surfaces with a variety of paint finishes
- In most circumstances one coat of paint is enough to produce an excellent finish
- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.02m
- Highly flame retardant as per DIN 4102-B1 when used on mineral base surfaces
- Does not contain PVC, softeners and solvents
- Does not contain fibre glass
- Does not contain heavy metal compounds and formaldehyde
- Dimensionally stable and covers over cracks
- Very hard-wearing when used with an appropriate paint
- Dry-strippable when hung using an appropriate 'paste the wall' adhesive
- Produces a sound base for paint, printed wallpaper or plaster
- Can be painted over several times with commercial paints

Application/Hanging

ERFURT-Variovlies® M 140 Objekt when used as a base surface for painting:

Excellent performance, even on old and cracked plaster or similar which is to be painted after preparation. Also creates a smooth flat surface where the base surface is made up of a variety of different materials e.g. plaster, exposed concrete or plasterboard.

Use nonwoven adhesive (e.g. Metylan NP New Plaster Paste in a ratio of 1:10 i.e. 1 kg in 10 l water or Metylan NP Power Granulate Plus in a ratio of 1:12 i.e. 1 kg in 12 l water or using 'paste the wall' technique in a ratio of 1:10 i.e. 1 kg in 10 l water) or a similar good quality paste suitable for 'paste the wall' products.

ERFURT-Variovlies® M 140 Objekt does not need soaking before hanging. Hang ERFURT-Variovlies® M 140 Objekt vertically using butt joints. Use a good quality emulsion paint including water or shower-proof emulsion paint (DIN EN 13300) when appropriate.

ERFURT-Variovlies® M 140 Objekt as a base surface for wallpaper:

Use adhesive suitable for the particular wall covering, however we recommend that at the very least, paste in a ratio of 1:20 (200g in 4 l water), for this application. Thanks to the stability of ERFURT-Variovlies® M 140 Objekt, all wall coverings applied over it can be removed when later redecorating without damaging the base surface.

ERFURT-Variovlies® M 140 Objekt can be covered again and again.

ERFURT-Variovlies® M 140 Objekt on problem base surfaces:

Where problem base surfaces are encountered, such as varnished and synthetic coatings or even residual adhesive, use 'paste the wall' technique and Metylan Ovalit V (or similar high performance adhesive) to achieve a smooth base surface in preparation for paint or printed wallpaper.

Dry-strippable

ERFURT-Variovlies® M 140 Objekt is fully dry-strippable when applied with a suitable paste (not, however Metylan Ovalit V or Ovalit P).

Ingredients/Test Results

ERFURT-Variovlies® M 140 Objekt is regularly tested in accordance with the Food and Consumer Goods Act § 30 and § 31.

The Declaration of No Objection (20535 U 04 by the ISEGA Research and Testing Co.Ltd., Aschaffenburg) confirms that ERFURT-Variovlies® M 140 Objekt meets the requirements of the Food and Consumer Goods Act as well as Recommendation 36 of the Federal German Office of Health.

The water vapour permeability was determined by Test Report No. 1743/32 in accordance with DIN 52615 Part 1.