



Product advantages



No soaking required



'Paste the wall'



Easy to paint



Economical paint surface



Knock-resistant



Covers cracks



Active-breathing



PVC-free



Flame retardant



Dry-strippable



Nonwoven adhesive

Hanging instructions

1. Remove old wallpaper and paint. Smooth rough base surfaces with filler. Prime highly-absorbent base surfaces with solvent-free primer.



5. Trim off the excess material with a knife and a straight edge where it meets the ceiling, skirting boards or windows.

2a. Use a pasting machine or paste table – no soaking required or



6. Trim the wallpaper at corners and edges and butt the next length up to it.

2b. 'paste the wall' and apply. No soaking required.



7. Allow to dry before applying 1 or 2 coats of high-quality emulsion paint (DIN EN 13300) or acrylic gloss if desired.

3. Butt the lengths together.



8. The wallpaper can easily be dry-stripped when you come to redecorate.

4. Smooth down the wallpaper using a sponge roller.



Product description

Manufacturer

Erfurt & Sohn KG
Hugo-Erfurt-Straße 1
42399 Wuppertal
www.erfurt.com

Product name

ERFURT-Variovlies® V 180

Raw materials/Manufacture

ERFURT-Variovlies® V 180 is a hard-wearing wall covering, with a pre-coated surface, manufactured from special cellulose and textile fibres, combined with polymer binding agents.

Product data

- Order no. 762
- Roll dimensions: 25 m long x 0.75 m wide
- Carton content: 2 rolls
- Weight: approx. 180 g/m²
- Edge-trimmed and wrapped in film

Product features

- Pre-coated wall covering
- The water-vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer density of 0.05 m
- Highly flame retardant as per DIN 4102-B1 when used on mineral base surfaces
- Does not contain PVC, softeners and solvents
- Does not contain fibre glass
- Does not contain heavy metal compounds and formaldehyde
- Dimensionally stable and covers over cracks
- Very hard-wearing when used with an appropriate paint
- Very good base surface coverage owing to its pigmentation – one coat of paint is usually enough
- Can be painted over several times with commercial paints
- Full dry-strippable when applied with a suitable adhesive

Application/Hanging

ERFURT-Variovlies® V 180 can be used on all indoor base surfaces where a painted finish is required. Given its smooth surface, the base surface must be carefully prepared and must be dry, clean and firm. The smoother the base surface, the better the result will be.

Remove old wallpaper and peeling paint. Smooth rough base surfaces with filler. Prime highly-absorbent base surfaces with solvent-free primer. For more guidance refer to BSG Information Leaflets 7 and 16.

Using 'paste the wall' technique

Use nonwoven adhesive (e.g. Metylan NP New Plaster Paste in a ratio of 1:10 i.e. 1 kg in 10 l water or Metylan NP Power Granulate Plus in a ratio of 1:10 i.e. 1 kg in 10 l water) or a similar good quality product.

The adhesive/paste is applied evenly to the base surface and the cut lengths are applied dry onto the pasted surface. Please note the adhesive manufacturer's instructions.

Using a pasting machine or pasting table

ERFURT-Variovlies® V 180 can also be pasted before hanging, folded and then hung without any soaking. Use an adhesive (e.g. Metylan NP New Plaster Paste in a ratio of 1:10 i.e. 1 kg in 10 l water or Metylan NP Power Granulate Plus in a ratio of 1:12 i.e. 1 kg in 12 l water) or a similar product suitable for 'paste the wall' products. Please note the adhesive manufacturer's instructions.

Hanging

Hang ERFURT-Variovlies® V 180 vertically with a butt joint. Press the lengths down using a rubber roller or wallpapering spatula until they are free of bubbles. Press excess paper into the corners under ceilings, at skirting and windows using a plastic spatula and cut off with a knife. Do not overlap the wall covering. Remove any adhesive on the surface immediately.

Painting

Allow the ERFURT-Variovlies® V 180 to dry before applying paint, usually one coat of paint will be adequate. Emulsion paint (DIN EN 13300), silk and high-gloss latex paints are suitable for use.

Dry-strippable

ERFURT-Variovlies® V 180 is fully dry-strippable when later redecorating.

Ingredients/Test Results

ERFURT-Variovlies® V 180 is regularly tested in accordance with the Food and Consumer Goods Act §§ 30 and 31.

The Declaration of No Objection (22409 U 06 by the ISEGA Research and Testing Co.Ltd., Aschaffenburg) confirms that ERFURT-Variovlies® V 180 meets the requirements of the Food and Consumer Goods Act as well as Recommendation 36 of the Federal German Office of Health.

The water vapour permeability was determined by ISEGA Research and Test Co. Ltd., Aschaffenburg with Test Report No.1743/37 in accordance with DIN 52615 Part 1.