GB

ERFURT-Vliesfaser Ready

ERFURT®
WÄNDE ZUM WOHLFÜHLEN

Product benefits

- PVC-free
- Fire-retardant
- For walls and ceilings
- Paintable
- Breathable
- No soaking
- Nonwoven adhesive
- Paste-the-wall technique
- Covers cracks
- Easy to remove
- No painting required

How to use

1. Make sure that the base surface is dry, firm, clean, plain-coloured and smooth. Remove old wallcoverings and loose coatings. Smooth out rough base surfaces with plaster-based filler. Use a suitable primer to create an evenly absorbent base surface.

2a. Cut the strips to the required length allowing an additional margin of 5 - 10 cm. Stir the paste according to the manufacturer's instructions

2b. and use a pasting machine or the paste-the-wall technique with nonwoven wallcoverings.



3. Hang the lengths perpendicularly and butt jointed and use a wallpapering brush or wallpapering roller to smooth out any bubbles. Remove any flecks of paste from the surface. Do not overlap the lengths.

4. Use a Stanley knife and wallpapering palette knife to trim off excess material at ceilings, skirting boards or windows etc.

5. Do not overlap in corners and at edges, but separate precisely along the edge and butt joint the next length.



6. ERFURT-Vliesfaser Ready nonwoven is pre-painted. No painting is required once it has been applied. You can apply a coat of paint of your choice to the finished wallcovering, if required, ideally an emulsion paint (min. wet abrasion class 3 in line with DIN EN 13300).

Vliesfaser

www.erfurt.com

GB

Technical Data Sheet 03/2025

Product description

ERFURT-Vliesfaser Ready

Product description

ERFURT ready-to-use Vliesfaser Ready is a lightly embossed nonwoven wallcovering that has been developed for its durability and ease of use. ERFURT-Vliesfaser Ready is a white printed ready-to-use wallcovering that can be used straight from the roll. If you wish to, you can apply a coat of water-based paint in the colour of your choice. Vliesfaser Ready nonwoven is dimensionally stable and covers cracks (hair and spreading cracks).

Manufacturer:

ERFURT & SOHN KG • Hugo-Erfurt-Strasse 1
42399 Wuppertal • GERMANY • www.erfurt.com

Manufacture

High-quality raw materials are used in its manufacture. All Vliesfaser-Ready nonwoven wallcoverings are made from cellulose and textile fibres that are embossed to create a unique pattern. The texture is produced without the use of PVC and plasticisers.

Product specification

Surface weight: approx. 140 g/m²
Roll dimensions: 10.05 m x 0.53 m
Box contents: 6 rolls
Carbon neutral by compensation.

Product benefits

- White printed nonwoven wallpaper
- No painting required
- Highly scratch-resistant without painting
- High-quality, lightly embossed surface
- Hang without the need for soaking
- Especially suitable for use with the paste-the-wall technique
- Easy to remove
- Free of PVC and plasticisers
- Tolerated by the skin - fibreglass-free
- Breathable
- Can be re-painted several times
- Easy to apply
- Covers cracks – class A1 cracks
- Particularly low-emission

Recommended paste

Hang with ERFURT Nonwoven Wallpaper Paste (200 g in 5 litres of water for approx. 25 m²). Alternatively: paste for nonwoven wallpaper. Refer to the manufacturer's instructions!

Base surface

ERFURT-Vliesfaser Ready can be used on all interior base surfaces suitable for wallpapering. Ensure that the base surface is dry, firm, evenly absorbent, clean, smooth, plain-coloured and sufficiently even for the intended wallcovering. Remove old wallcoverings and loose coatings. Smooth out rough base surfaces with plaster-based filler. Prime smooth plaster with diluted paste. Use suitable primers to pre-treat very absorbent base surfaces or base surfaces with different levels of absorbency. An evenly coloured base surface is required as Vliesfaser Ready is a ready-to-use wallcovering.

How to use

ERFURT-Vliesfaser Ready nonwoven wallcoverings can be applied using the paste-the-wall technique or a pasting machine. Pay attention to the correct amount and even distribution of paste when applying it. Applying too much paste can lead to the accumulation of paste resulting in a flawed appearance and seam marks caused by seams opening up during drying. Cut the lengths of ERFURT-Vliesfaser Ready nonwoven wallcovering to the height of the wall plus an extra margin. Apply perpendicularly and butt-jointed. Smooth out the bubbles with a wallpapering roller or a wallpapering brush. Use a wallpapering palette knife to press any excess material at ceilings, skirtings, windows etc. into the corners and cut off with a Stanley knife or scissors. Do not overlap the lengths of ERFURT-Vliesfaser Ready nonwoven. We recommend using wallpapering corner profiles with external corners that are not perpendicular. The ERFURT-Vliesfaser Ready wallcovering needs to be cut exactly at the edge if you do not wish to use wallpapering corner profiles. ERFURT-Vliesfaser Ready can be applied around the corner for perpendicular external corners (a minimum of 10 cm). Immediately remove fresh paste marks with a damp sponge/cloth. Avoid draughts and excessive heating of the room when drying. Rapid drying can lead to openings along the seam, which will become visible when the wallcovering is subsequently painted. Do not work with an air or building temperature of below + 10 °C.

Painting/Coating

If you wish to apply a coat of paint at a later date, an emulsion paint (minimum wet abrasion class 3 according to DIN 13300) can be applied to the Vliesfaser Ready nonwoven wallcovering, depending on the level of wear and tear. Always paint the wallcovering quickly and without interruption. Satin gloss paints really accentuate the embossed texture of the wallcovering.

Renovation

ERFURT-Vliesfaser Ready wallcoverings can be repainted when you come to redecorate. The wallcovering is easy to remove if it has been applied properly.

Storage

Store the rolls of wallcovering standing upright in a dry and cool place.

Quality seal

Vliesfaser Ready nonwoven wallcoverings meet all the relevant standards and the most exacting quality requirements. Various product properties of Vliesfaser wallcoverings are regularly tested and certified by independent test institutes. The following tests / certifications apply:

- **EPD:** Environmental Product Declaration; Group test by the Global Wallcoverings Association (IGI)
- **VOC content:**
  - Complies with the AgBB Standard emission test: extremely low-emission.
  - Conforms to the French emission test in line with Décret-No. 2011-321+ CMR Regulation (A+)
- **Its water vapour permeability** as per DIN EN ISO 12572:2017-05 corresponds to a diffusion-equivalent air layer thickness of approximately 0.04 m.
- **Fire behaviour classification:** C-s1,d0 according to DIN EN 13501-1 (fire-retardant)

Important note

- Material testing: Only apply the identical manufacturing batch number of identically patterned Vliesfaser Ready wallcoverings to a wall. Check the rolls for possible material defects before using. Only apply rolls with the same dimensions together.
- Wallpapering waste can be disposed of with normal household waste.

  Disposal key:
  Waste category: Construction site waste
  Waste key: 17 09 04
- If you come across a defect when applying the wallcovering, stop working immediately and contact your retailer. Complaints without evidence (sample pieces and package slip) cannot be accepted. The above information represents only general recommendations.
- As the application and use of this product lies outside our influence, our information does not relieve our customers of the need to check our products for their suitability for the intended processes and purposes. This issue will lose its validity with the publication of a new issue due to technical advances.

Made in Germany
ERFURT & SOHN KG
Hugo-Erfurt-Strasse 1
42399 Wuppertal, Germany
Tel.: +49 202 6110 0
Fax: +49 202 6110 89 451
E-mail: info@erfurt.com
Website: **www.erfurt.com**

ERFURT®
WÄNDE ZUM WOHLFÜHLEN