




Product benefits




PVC-free



Fire-retardant



For walls and ceilings



Easy to re-paint




Breathable




Impact-resistant



No soaking




Nonwoven adhesive




Paste-the-wall technique



Low paint consumption



Covers cracks



Easy to remove

How to use



1. Remove old wallpaper and paint. Smooth rough base surfaces with plaster-based filler. Prime very absorbent base surfaces with solvent-free primer.



2a. Use with the paste-the-wall technique – no soaking. Or



2b. Use a pasting machine without soaking.



3. Hang perpendicular, with the lengths butted jointed to each other.



4. Press the widths free of bubbles using a wallpapering brush or rubber roller.



5. Use a Stanley knife and wallpapering palette knife to trim off excess material at ceilings, skirting boards or windows etc.



6. Do not overlap in corners and at edges, but separate precisely along the edge and butt joint the next length.



7. When dry, paint with high-quality emulsion paint in line with EN 13300 or possibly plaster or wallpaper etc.



Technical Data Sheet 10/2015

Product Description

ERFURT-Variovlies Plano

Manufacturer

ERFURT & SOHN KG • Hugo-Erfurt-Straße 1
42399 Wuppertal • GERMANY • www.erfurt.com

Raw materials/Manufacture

ERFURT-Variovlies Plano is a flat wallcovering, manufactured from recycled paper and textile fibres.

Product data

- Order no. 1000629
- Roll dimensions: 20.00 m long x 0.53 m wide
- Carton content: 9 rolls
- Weight: approx. 150 g/m²
- Order no. 1000632
- Roll dimensions: 15.00 m long x 0.75 m wide
- Carton content: 6 rolls
- Weight: approx. 150 g/m²

Product features

- Covers contrasting colours on base surfaces very well
- Its water vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer thickness of approximately 0.02 m.
- Fire rating "B-s1,d0" according to EN 13501-1 corresponds to "B1" (fire-retardant) according to DIN 4102-1
- The composite material is non-flammable on base surfaces, such as plasterboard (DIN 4102-A2)
- Free of PVC, plasticisers and solvents harmful to health
- Fibreglass-free
- No heavy metal compounds or formaldehyde added
- Covers cracks
- Conserves resources
- Breathable
- Made of sustainable raw materials
- Suitable for allergy-sufferers
- Can be re-painted several times with commercially available emulsion paints
- Easy to remove after moistening with water

Application/Handling

ERFURT-Variovlies Plano can be used on all interior base surfaces suitable for wallpapering. The base surface must be dry, clean, firm, slightly absorbent and smooth. Remove old wallpaper and loose paint. Smooth rough base surfaces with gypsum plaster. Prime very absorbent base surfaces with solvent-free primer.

Using the paste-the-wall technique

Use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Apply the adhesive evenly to the base surface and place the cut lengths dry into the bed of adhesive. Please read the adhesive manufacturer's instructions for use.

Using a pasting machine

ERFURT-Variovlies Plano can also be pasted using a pasting machine, folded together and applied without soaking. Use nonwoven adhesive (e.g. Metylan Secura 1:10 = 500 g in 5 l water) or a comparable product. Please read the adhesive manufacturer's instructions for use.

Wallpapering

Hang ERFURT-Variovlies Plano perpendicular, with the lengths butt jointed to each other. Press the widths free of bubbles using a rubber roller or a wallpapering palette knife. Press excess lengths at ceilings, skirtings, windows etc. into the corners with a straight edge and cut off with a Stanley knife. Ensure that the wallcovering does not overlap. Immediately remove any traces of adhesive from the surface.

Painting

After drying, ERFURT-Variovlies Plano should be painted or coated. A high-grade emulsion paint can be used for this.

Ingredients/Test results

Its water vapour permeability was certified by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH in Aschaffenburg, Germany and conforms to DIN 52615 Section 1 with Test Report 1743/42.

Made in Germany

ERFURT & SOHN KG
Hugo-Erfurt-Straße 1
D-42399 Wuppertal

Tel.: +49 202 6110 0
Fax: +49 202 6110 89 451

E-mail: info@erfurt.com
Internet: www.erfurt.com

Service line:
+49 202 6110 375

ERFURT
WÄNDE ZUM WOHLFÜHLEN