



ERFURT-Variovlies V 130

ERFURT
WÄNDE ZUM WOHLFÜHLEN

FLAT NONWOVEN
WALLPAPER

Product benefits




PVC-free



Non-flammable



For walls and ceilings




Can be re-painted several times




Breathable



No soaking




Nonwoven adhesive



Paste-the-wall technique



Minimal paint usage



Covers cracks



Easy to remove

How to use



1. Remove old wallpaper and paint. Smooth rough base surfaces with plaster-based filler. Prime very absorbent base surfaces with solvent-free primer.




2 a. Use a pasting machine without soaking. Or



2b. Use with the paste-the-wall technique – no soaking



3. Hang perpendicular, with the lengths butted jointed to each other.




4. Press the widths free of bubbles using a wall-papering brush or rubber roller.



5. Use a Stanley knife and palette knife to trim off excess material at ceilings, skirting boards or windows etc.



6. Do not overlap in corners and at edges, but separate precisely along the edge and butt joint the next length.



7. When dry, apply high-quality emulsion paint (DIN EN 13300-compliant) or acrylic coating.



8. When you come to redecorate, the wallpaper can be removed with ease.

Variovlies

PRO

www.erfurt.com



Product Description

ERFURT-Variolvies V 130

Manufacturer

ERFURT & SOHN KG • Hugo-Erfurt-Straße 1
42399 Wuppertal • GERMANY • www.erfurt.com

Raw materials/Manufacture

ERFURT-Variolvies V 130 is a durable wall covering with a pre-pigmented surface, made of special cellulose and textile fibres, combined with polymer binding agents.

Product data

- Order no. 1002860
- Roll dimensions: 50.00 m long x 0.75 m wide
- Carton content: 2 rolls
- Weight: approx. 130 g/m²
- Order no. 1002861
- Roll dimensions: 25.00 m long x 1.00 m wide
- Carton content: 4 rolls
- Weight: approx. 130 g/m²

Product features

- Its water vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer thickness of approximately 0.05 m
- Fire rating "B-s1,d0" according to DIN EN 13501-1 (fire-retardant)
- Pre-pigmented wallcovering
- Free of PVC, plasticisers and solvents harmful to health
- Fibreglass-free
- No heavy metal compounds or formaldehyde added
- Dimensionally stable and covers cracks
- Very durable when used with corresponding paints
- Excellent base surface coverage by pigmentation, therefore one coat generally suffices in most cases
- Can be re-painted several times with commercially available paints
- Easy to remove after moistening with water

Application/Handling

Base surface

ERFURT-Variolvies V 130 can be used on all interior base surfaces suitable for wallpapering, which should be painted after appropriate preparatory work. Ensure that the base surface is dry, firm, even, absorbent, clean, smooth and sufficiently even for the intended wallcovering. Remove old wallpaper and loose paint. Smooth out rough base surfaces with plaster-based filler. Prime smooth plaster with diluted paste. Please read BFS data sheets nos. 7 and 16.

Adhesive

Henkel: Solvite Ready to Roll, Delicate Wallcoverings Adhesive

Pufas: Glutolin S15, Glutolin K10, Decotric GK

Wallpapering

Hang ERFURT-Variolvies V 130 perpendicular, with the lengths butt jointed to each other. Smooth out the bubbles with a rubber roller or a wallpapering palette knife. Press excess lengths at ceilings, skirtings, windows etc. into the corners with a straight edge and cut off with a Stanley knife. Ensure that the wallcovering does not overlap. Immediately remove any traces of adhesive from the surface.

Painting

After drying, in most cases only one coat is needed with ERFURT-Variolvies V 130 due to its pre-pigmentation. Emulsion paint with minimum wet abrasion class 3 (as per DIN EN 13300) in particular, satin and high-gloss latex paints, are suitable.

Alternatively the wallpapered surface can be painted in an airless process. If doing so, it is necessary to subsequently roll the surface with a short pile paint roller to obtain a clean and even appearance.

Made in Germany

ERFURT & SOHN KG
Hugo-Erfurt-Straße 1
42399 Wuppertal

Tel.: +49 202 6110 0
Fax: +49 202 6110 89 451

E-mail: info@erfurt.com
Internet: www.erfurt.com

ERFURT
WÄNDE ZUM WOHLFÜHLEN