



ERFURT-Variovlies V 200 S

ERFURT
WÄNDE ZUM WOHLFÜHLEN

GLATTVLIES-
TAPETEN


Product benefits




PVC-free



Fire-retardant



For walls and ceilings



Can be re-painted several times




Breathable




Impact-resistant



No soaking




Nonwoven adhesive




Paste-the-wall technique



Minimal paint usage



Covers cracks



Easy to remove

How to use



1. Remove old wallpaper and paint. Smooth out rough base surfaces with plaster-based filler. Prime very absorbent base surfaces with solvent-free primer.



2a. Use a pasting machine without soaking or



2b. Use with the paste-the-wall technique without soaking



3. Hang perpendicular, with the lengths butted jointed to each other.



4. Use a wallpapering brush or rubber roller to press out bubbles and folds.



5. Use a Stanley knife and palette knife to trim off excess material at ceilings, skirting boards or windows etc.



6. Do not overlap in corners and at edges, but separate precisely along the edge and butt joint the next length.



7. When dry, apply high-quality emulsion paint (EN 13300-compliant) or acrylic coating.



8. When you come to redecorate, the wallpaper can be removed with ease.

Variovlies

PRO

www.erfurt.com



Product Description

ERFURT-Variovlies V 200 S

Manufacturer

ERFURT & SOHN KG • Hugo-Erfurt-Straße 1
42399 Wuppertal • GERMANY • www.erfurt.com

Raw materials/Manufacture

ERFURT-Variovlies V 200 S is a durable wallcovering with an extremely flat surface, made of special cellulose and textile fibres, combined with polymer binding agents.

Product data

- Order no. 1000555
- Roll dimensions: 25.00 m long x 0.75 m wide
- Carton content: 2 rolls
- Weight: approx. 200 g/m²

Product features

- Its water vapour permeability as per DIN 52615 corresponds to a diffusion-equivalent air layer thickness of approx. 0.08 m.
- Fire rating „B-s1,d0“ according to EN 13501-1 corresponds to „B1“ (fire-retardant) according to DIN 4102-1
- Smooth, silk, coated, satin finish
- The composite material is non-flammable on base surfaces, like plasterboard (EN A2-s1,d0).
- Free of PVC, plasticisers and solvents harmful to health
- Fibreglass-free
- No addition of heavy metal compounds or formaldehyde
- Dimensionally stable and covers cracks
- Very durable when used with appropriate paints
- Excellent base surface coverage by pigmentation, therefore one coat generally suffices
- Can be re-painted several times with commercially available paints
- Easy to remove after moistening with water

Application/Handling

Base surface

ERFURT-Variovlies V 200 S can be used on all interior base surfaces that can be wallpapered, which should be painted after appropriate preparatory work. Prepare the base surface very carefully in advance owing to the extremely smooth surface of the paper and ensure it is dry, clean, solid, slightly absorbent and smooth.

Ensure that the base surface is dry, firm, even, absorbent, clean, smooth and sufficiently even for the intended wallcovering. Remove old wallpaper and loose paint. Smooth out rough base surfaces with plaster-based filler. Prime smooth plaster with diluted paste. Prime very absorbent base surfaces with solvent-free primers. Remove old wallpaper and loose paint. Please read BFS data sheets nos. 7 and 16.

Adhesive

For covering cracks and for wall design:

Henkel: Solvite Ready to Roll, Delicate Wallcoverings Adhesive

Pufas: Glutolin S15, Glutolin K10, Decotric GK

On non-absorbent base surfaces, such as plastic walls:

Pufas: Glutolin BW, Decotric WB

Adhesion

Hang ERFURT-Variovlies V 200 S perpendicular, with the lengths butt jointed to each other. Smooth out the bubbles with a rubber roller or a wallpapering palette knife. Press excess lengths at ceilings, skirtings, windows etc. into the corners with a wallpapering palette knife and cut off with a Stanley knife. Do not hang the wallcovering overlapping. Immediately remove any traces of adhesive from the surface.

Painting

After drying, paint over ERFURT-Variovlies V 200 S. Use emulsion paint with minimum wet abrasion class 2 (as per EN 13300). Two coats of paint are needed for high-gloss finishes.

Ingredients/Test results

Its water vapour permeability as per DIN 52615 was certified by the ISEGA-Forschungs- und Untersuchungs-Gesellschaft mbH in Aschaffenburg, Germany.

Made in Germany

ERFURT & SOHN KG
Hugo-Erfurt-Straße 1
42399 Wuppertal

Phone.: +49 202 6110 0
Fax: +49 202 6110 89 451

E-mail: info@erfurt.com
Website: www.erfurt.com

Service line:
+49 202 6110 375

ERFURT
WÄNDE ZUM WOHLFÜHLEN