

Revision: 17.10.2023



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2023

Version number 17

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- · Trade name: Erfurt Systemkleber SR6
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Cementitious fine mortar
- · Uses advised against Applications not mentioned above are not recommended.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Erfurt & Sohn KG' Wände zum Wohlfühlen Hugo-Erfurt-Straße 1 42399 Wuppertal

www.erfurt.com

Informing department:

Ansprechpartner Herr Stephan Schmieder

Telefon: +49 (202) 6110 - 420 E-Mail: s.schmieder@erfurt.com 1.4 Emergency telephone number:

Poisen centre Bonn (Germany): +49 (228) 19240 (24h available)

### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

- · Hazard pictograms GHS05, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling:

Cement, portland, chemicals calcium dihydroxide

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

· Precautionary statements

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 17 Revision: 17.10.2023

Trade name: Erfurt Systemkleber SR6

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362 Take off contaminated clothing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures

· Description: Product based on cement and mineral filler.

· Dangerous components:

CAS: 65997-15-1 Cement, portland, chemicals 50-100%

EINECS: 266-043-4 📀 Eye Dam. 1, H318; 🗘 Skin Irrit. 2, H315; STOT SE 3, H335

CAS: 1305-62-0 calcium dihydroxide

<2.5%

EINECS: 215-137-3 < Eye Dam. 1, H318; 🗘 Skin Irrit. 2, H315; STOT SE 3, H335

Additional information

The chromate content in cement is less than 2 ppm so that the labelling with H317 is not applicable (1907/2006/EG, Annex XVII (47)).

For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · General information Personal protection for the First Aider.
- · After inhalation Supply fresh air or oxygen; call for doctor.
- · After skin contact

Instantly wash with water and soap and rinse thoroughly.

After contact, clean the skin mechanical and rinse with water and soap.

- After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing

Drink copious amounts of water and provide fresh air. Instantly call for doctor.

Show the packaging or the label to the doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: Wear personal protective clothing.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 17 Revision: 17.10.2023

Trade name: Erfurt Systemkleber SR6

Follow the emergency-plan.

(Contd. of page 2)

### **SECTION 6: Accidental release measures**

 6.1 Personal precautions, protective equipment and emergency procedures Bring persons out of danger.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Pick up the product mechanically, avoid dust formation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

### **SECTION 7: Handling and storage**

7.1 Precautions for safe handling

Thorough dedusting.

Prevent formation of dust.

Keep away from children.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility:

Please follow the rules of the VCI-Storage-Concept for chemicals.

· Further information about storage conditions:

Keep container tightly sealed.

Store in a locked cabinet and out of the reach of children.

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- Components with critical values that require monitoring at the workplace:

### 65997-15-1 Cement, portland, chemicals (50-100%)

WEL Long-term value: 10\* 4\*\* mg/m³ \*inhalable dust \*\*respirable dust

### 1305-62-0 calcium dihydroxide (<2.5%)

WEL Short-term value: 4\* mg/m³ Long-term value: 5 1\* mg/m³

\*resprable fraction

- · Additional information: The lists that were valid during the compilation were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls

It must be possible to wash the skin in the working area.

Eye-wash bottle must be available.

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

(Contd. on page 4)

(Contd. of page 3)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 17 Revision: 17.10.2023

Trade name: Erfurt Systemkleber SR6

Keep away from foodstuffs, beverages and food.

Vacuum clean contaminated clothing. Do not blow or brush off contamination.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Be sure to clean skin thoroughly after work and before breaks.

· Breathing equipment: Use breathing protection in case of insufficient ventilation.

· Hand protection

Do not reuse one-way-gloves

Hand Protection: Nitril-rubber-latex-gloves.

In case of wearing synthetic protective gloves use cotton-gloves as underwear.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

Gloves made of: Nitrile rubber, butyl rubber.

(Category 3 chemical protective gloves, recognisable by the CE mark with four-digit test number). When wearing protective gloves, cotton undergloves are recommended.

For activities using products containing cement, suitable protective gloves have been identified (GISCODES ZP1). Suitable are, for example

Ampri: SolidSafety Cut 081101 / SolidSafety Tough 081201 / SolidSafetyTough Dots 081202

Ansell: Flexitril L27 / Fleximax 27 or 35 / Hylite / Nitrotough N210 / Sol-Knit

KCL: Sahara / Gobi / Nitex

MAPA: Duo-Mix 405 / Enduro 328 / Stansolv AK 22 / Titanlite 397 / Titansuperlite

UVEX: uvex Profi Ergo XG 20 / uvex phynomic pro

### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

### · Eye/face protection

Tightly sealed safety glasses.

In case of splashing use protecting basket-glasses.

### · Body protection:

Contaminated protection clothes must be cleaned carefully before reuse.

Protective work clothing.

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

· General Information

· Physical state Solid material.

· Colour: Grev

· Smell: Weak, characteristic · Odour threshold: Not determined. Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range not apply

· Flammability Not determined.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable · Decomposition temperature: Not determined.

· pH at 20 °C 11.6 (1%) · Viscosity:

Kinematic viscosity

Not applicable.

(Contd. on page 5)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 17 Revision: 17.10.2023

Trade name: Erfurt Systemkleber SR6

(Contd. of page 4)

· **dynamic:** Not applicable.

· Solubility

· Water: miscible

· Partition coefficient n-octanol/water (log

value) Not determined.
Steam pressure: Not applicable.

· Density and/or relative density

Density
 Relative density
 Settled apparent density
 Vapour density
 bulk density
 Not determined.
 0.8 kg/dm³
 Not applicable.

9.2 Other information

· Appearance:

· Form: Powder

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

· Solvent content:

· Organic solvents: 0.0 %

· Change in condition

· Evaporation rate Not applicable.

Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void

flammable gases in contact with water

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Ovoid
Void
Void
Void
Void

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 17 Revision: 17.10.2023

Trade name: Erfurt Systemkleber SR6

(Contd. of page 5)

### **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

### 1305-62-0 calcium dihydroxide

Oral LD50 7,340 mg/kg (rats)

Dermal LD50 >2,500 mg/kg (Kan) (OECD 402)

### 544-17-2 Calciumformiat

Oral LD50 3,050 mg/kg (rats) (OECD 401)
Dermal LD50 >2,000 mg/kg (rats) (OECD 402)

### 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Oral LD50 >5,000 mg/kg (rats)
Dermal LD50 >5,000 mg/kg (Kan)

Inhalative LC50/4 h >5 mg/l (rats)

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-single exposure May cause respiratory irritation.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity:

### 1305-62-0 calcium dihydroxide

EC50 (48h) 49.1 mg/l (Daphnia magna)

### 544-17-2 Calciumformiat

LC 0 >1,000 mg/l /48h (Brachydanio rerio)

EC50 (48h) >1,000 mg/l (Daphnia magna) (EPA-660/3-75-009)

EC50 >1,000 mg/l /72h (Pseudokirchneriella subcapitata) (ASTM E-47.01)

NOEC ≥100 mg/l /21d (Daphnia magna) (OECD 211)

≥22.1 mg/l /29d (bacterial toxicity) (OECD 306)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

# Safety data sheet

according to 1907/2006/EC, Article 31

Version number 17

Trade name: Erfurt Systemkleber SR6

(Contd. of page 6)

Revision: 17.10.2023

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Printing date 17.10.2023

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleaning agent: Water, if necessary with cleaning agent.

44.4.1101 1 10 1	
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
· · · · ·	VOIM
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA	Void
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according	ng to
IMO instruments	Not applicable.
UN "Model Regulation":	Void

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

- Department issuing data specification sheet: Environment protection department.
- · Contact: Hr. S. Schmieder
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 8)

(Contd. of page 7)

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 17 Revision: 17.10.2023

Trade name: Erfurt Systemkleber SR6

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.